


**IG5940**

IGK3005-BPKG/US-104-DPS

Inductive sensors



**Product characteristics**

Inductive sensor
Metal thread M18 x 1
Connector
Gold-plated contacts
Sensing range 5 mm; [f] flush mountable

**Electrical data**

Electrical design	DC PNP
Operating voltage [V]	10...30 DC
Current consumption [mA]	< 10
Protection class	II
Reverse polarity protection	yes

**Outputs**

Output function	normally open
Voltage drop [V]	< 2.5
Current rating [mA]	250
Short-circuit protection	yes
Overload protection	yes
Switching frequency [Hz]	500

**Range**

Sensing range [mm]	5
Real sensing range (Sr) [mm]	5 ± 10 %
Operating distance [mm]	0...4.05

**Accuracy / deviations**

Correction factors	mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.5 / Al approx. 0.4 / Cu approx. 0.3
Hysteresis [% of Sr]	3...15
Switch-point drift [% of Sr]	-10...10

**Environment**

Ambient temperature [°C]	-25...80
Protection	IP 67

**Tests / approvals**

EMC	EN 60947-5-2 EN 55011: class B
MTTF [Years]	1862

**Mechanical data**

Mounting	flush mountable
----------	-----------------

## IG5940

IGK3005-BPKG/US-104-DPS

Inductive sensors

Housing materials	Brass white bronze coated; active face: PBT orange; LED window: PEI; lock nuts: Brass white bronze coated
-------------------	---

Weight	[kg]	0.052
--------	------	-------


### Displays / operating elements

Output status indication	LED	4 x yellow
--------------------------	-----	------------

### Electrical connection

Connection	M12 connector; Gold-plated contacts
------------	-------------------------------------

### Wiring



### Accessories

Accessories (included)	2 lock nuts
------------------------	-------------

### Remarks

Pack quantity	[piece]	1
---------------	---------	---